



Material Safety Data Sheet

Section 01: Product & Company Identification

Product Name: RUBBERIZED CRACK FILLER

Manufacturer: Innovative Group of Companies **Effective date:** November, 2009

78 Orchard Road,
Ajax, Ontario,
LIS 6L1,
Canada.

Emergency Phone Number:
613-996-6666

24 Hours/Day: 7 Days/Week

For More Information Call:
1-800-387-5777
905-427-0318

Trade Name: Rubberized Crack filler
Material Uses: Cold applied crack filler
WHMIS Classification: Not Controlled
Chemical Family: Asphalt Emulsion

Section 2: Composition and Information on Ingredients

Components	CAS #	% by Weight
Asphalt	8052-42-4	55 to 65
Lignin Pitch	-	1 to 5
Stabilizer	-	1 to 5
Insert Fillers	-	1 to 5
Latex Rubber	-	1 to 5

Section 3: Physical Data

Physical state: Solid
Odor / Appearance: Petroleum Odor / Brown.
Odor Threshold: n/a
Specific Gravity: 1.0 to 1.02
pH: 9.5
Vapor Pressure: n/a
Solubility in Water: Not soluble in water
% Volatile: 40
Coefficient of water / oil Distribution: n/a
Vapor Density: n/a

Section 4:	Fire & Explosion Hazard
-------------------	------------------------------------

Flammability:	Yes
If yes under what Conditions:	Product will burn if all water has evaporated
Means of Extinguishing:	Carbon dioxide, dry chemical, foam, or water
Special Procedure:	Wear self contained breathing apparatus, full protective devices if entering confined area
Flash Point:	>100 for asphalt, T.A.G.
Upper Explosion Limit:	n/a
Lower Explosion Limit:	n/a
Auto Ignition temperature:	n/a
Sensitivity to Mechanical Impact:	n/a
Sensitivity to Static Discharge:	n/a

Section 5:	Reactivity Data
-------------------	------------------------

Chemical Stability:	Yes
If No Under What Conditions:	n/a
Incompatibility o other Substances:	Yes
If So, Which ones:	Strong oxidizers
Reactivity under What Conditions:	Hazardous polymerization will not occur.
Hazardous Decomposition Products:	Oxides of carbon

Section 6:	Health Hazards
-------------------	-----------------------

Route of Entry:	Skin Contact
Effect of Acute exposure to material:	n/a
Effect of Chronic exposure to material:	Prolonged or repeated exposure can cause liver or kidney damage
	Prolonged or repeated contact may cause skin irritation or dry scaly dermatitis
Exposure limit:	5mg/m ³
Synergetic Material:	Saponified pine resin is a mild allergen
Irritancy of Material:	Mild irritation of skin and mucous membranes
Sensitivity of Material:	None
Carcinogenetic, Reproductive Effect:	Carcinogenicity: No Ingredient listed by IARC

Section 7:	First AID Measures
-------------------	---------------------------

Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately
---------------------	----------------------------------------------------------------------------------------------------------------------------------------------------

Skin Contact:	Remove from skin by wiping and washing thoroughly with water
Inhalation:	Remove victim to fresh air. Seek medical attention immediately
Ingestion:	Take a lot of water to dilute stomach. Seek medical attention immediately

Section 8:	Preventative Measures
-------------------	------------------------------

Eye Contact:	Wear Splash Proof Safety Goggles.
Skin Contact:	Wear Rubber Gloves, Boots & Long Sleeve Shirt
Inhalation:	In enclosed areas wear air respirator
Engineering Controls:	No special ventilation required
Waste Disposal:	Place absorbent in enclosed containers. Dispose of in accordance with local laws and regulations
Handling Procedures & Equipment:	Wash skin and equipment with warm water
Storage requirement:	Store in cool place, between 10 – 30C, avoid freezing
Special Shipping information:	Protect from freezing

Section 9:	Preparation Information
-------------------	--------------------------------

Prepared By:	Innovative Group of Companies
Telephone #:	905-427-0318
Preparation Date:	November, 2009
Superseded Date:	March, 2006